

Temporal and Spatial Coherence of Shallow Water Acoustic Propagation

Harry DeFerrari
Jennifer Whylie

University_of Miami
hdeferrari@rsmas.miami.edu


Data Sets

(M-sequence $q=4$)

- **SW06**
 - Continuous transmission to SHRU receivers. 50 hours
→ temporal properties – fluctuations, coherence in time
 - Periodic transmission to SHARK VLA and HLA
→ spatial properties
- **FSPE** - Florida Straits Propagation Experiment
 - Continuous Transmission 2 -30 day periods.
→ temporal properties
- **AO** - Acoustic Observatory
 - Short 20 min Transmission 500 element - HLA
→ spatial properties 20 to 80 km.

Acoustic Observatory CALOPS Sept 07

Shipboard Suspended and Towed Transmissions




SW06 Experiments – Mid-Atlantic Bight

MSM




↑
19.7 km Range
85 m Depth
↓





VLA 16 phones




HLA 32 phones 468 m (15 m spacing)



Acoustic propagation shallow shelves inside of western boundary currents

Prograde vs Retrograde fronts









Seasonal
Internal Wave
Sub-inertial


Miami Sound Machine

$F_c = 100, 200, 400, 800, 1600, 3200$. Hz.


$B_w = 25, 50, 100, 200, 400, 800$.



Shark VLA 100 Hz. m-sequence



Transmission Loss (dB re 1m)



PE Model (first try)



Several extra modes

$C_b = 1715$ m/s Inversion

by K. Smith and J. Miller

(In the vicinity)

PE (second try)




Good Fit ! Above)

1595 m/s


Measurements by UW (direct method) sediment pool at site of experiment

1600 m/s !


PE Prediction of 800 Hz. Pulse Response




Measured - 1 Hour



Data Analysis



$$COH(t, \tau) = \frac{\langle |p(t) * p(t + \tau)|^2 \rangle_{\Delta t, \Delta T}}{\langle p(t)^2 \rangle_{\Delta t, \Delta T} \langle p(t + \tau)^2 \rangle_{\Delta t, \Delta T}}$$




Temporal Coherence and Phase Wrapping

$$COH(t, \tau) = \frac{\left\langle \left(p(t) * p(t + \tau) \right)^2 \right\rangle_{\Delta t, \Delta T}}{\left\langle p(t)^2 \right\rangle_{\Delta t, \Delta T} \left\langle p(t + \tau)^2 \right\rangle_{\Delta t, \Delta T}}$$

Coherence is a statistical measure of the change of a waveform with time

Causes:



2. Multimode interference
 - Separate modes
 3. Slow phase shifts of undistorted waveform
 - Compute for all phase shifts or phase track.
 4. Random waveform distortion
 - Unrecoverable
- COH varies from both slow phase shifts in time that cause multipath/mode cancellation and from true randomizing effects.
 - Both usually happen at the same time (Phase wrapping, Flatte)





$$PE = (\rho/2)\eta^2 N^2,$$

Where, N is the buoyancy frequency,


$$\text{and } \eta = T' / dT / dz .$$




Temperature (deg. C)




shru852 Temporal Coherence 100 Hz.Hr0200 7/29




shru852 Temporal Coherence 100 Hz.Hr 1200 7/29




shru2252 Temporal Coherence 100 Hz.Hr 2200 7/29




shru852 Temporal Coherence 100 Hz.Hr0800 7/30




shru852 Pulse Response 100 Hz. Hr 200 7/29




shru852 Pulse Response 100 Hz. Hr 1200 7/29



shru852 Temporal Coherence 100 Hz.Hr0200 7/29




shru852 Temporal Coherence 100 Hz.Hr 1200 7/29






SW06 Modes and Arrivals


Observed




Modeled




shru852 Temporal Coherence 100 Hz.Hr0200 7/29




shru852 Temporal Coherence 100 Hz.Hr 1200 7/29




shru252 Temporal Coherence 100 Hz.




shru853 Temporal Coherence 100 Hz.






Temporal Coherence



Temporal Coherence




Coherence time (.75 level)


	BRB Group		SBRB arrival	
800Hz.	mean → 2.1	max → 6.5 minutes	800Hz. mean → 2.8	max → 6.5 minutes
400Hz.	3.4	12.0	400Hz. 4.2	>30
200	8.3	> 30	200 15.0	>> 30

800 Hz.

shru3 sw53 Pulse Response 800 Hz.



shru3 sw53 Temporal Coherence 800 Hz.



Temporal Coherence

Low Frequency < 100 Hz.

- Bottom appears smooth.

- No mode distortion from scattering

- IW caused mode coupling is evident.

Mid – Frequencies $100 >, < 800$ Hz.


- Bottom scattering become important.

- Coherence times decrease with frequency


- Coherence times decrease with increasing mode number


High frequency > 1000 Hz.



- Signals are randomized by bottom scattering




NOAA 14 AVHRR - 3 Feb 1995









Temperature Data 10k Exp.



T-Tmean IW band (deg C/min)



ETA**2



Florida Strait Propagation Experiments

Transmissions

M-Sequences

Hour	Frequency
------	-----------

1	100
---	-----

2	200
---	-----

3	400
---	-----

4	800
---	-----

5	1600
---	------

6	3200
---	------

7	100
---	-----

repeat

*

*

28 days



Range

10km

20km

Reception

VLA

32 – Phones

Coherent Averaging
(1 min)

SHARP
Pulse compression

Pulse Responses
One per minute

Signal Processing of M-sequences:

- Synchronous sampling $n \times f$, $n = > 4$.
- Coherent averaging for 1 minute.
- Sharp Pulse Compression (SPC) - Hadamard Transforms - a matched filter operation that yields the pulse response instead of the correlation of the pulse response.

Result:

- Gain = $10 \log(M \times L)$, =36dB @400 Hz.
- 2x Improvement in time resolution.
- Transparent to end user - no time leakage.
- Robust and well documented.

Propagation Modeling


Identifying modes and arrivals

Propagation Modeling

Propagation Models


- PE
 - MMPE
- Normal Mode
 - PROSIM
 - SNAP
- SAFARI

Bottom Models




	Velocity (m/s)	Gradient (1/s)	Density (dB/km/Hz)	Loss (dB/km/Hz)	Shear (m/s)	Shear Loss (dB/km/Hz)
MONJO	1585	1.4	1.85	.30	300	3.3
MEASURED (cores)	1640	1.4	1.95	.30	300	6.3
CHAPMAN (inv)	1720	1.4	2.06	.60	300	6.3



PE Prediction of 800 Hz. Pulse Response




Measured - 1 Hour



SFTF 10 km range--Hour 140



SFTF 10 km range--Hour 140



$$\beta^{-1} = -\frac{\Delta s_{g,mn}}{\Delta s_{p,mn}}$$

Effects of an eddy

3. Produces a focusing sound speed profile for RBR Modes


- Deep source is amplified relative to shallow source
- Near perfect multipath recombination

4. Forms a duct for internal waves to propagate onto the shelf


- Orders of magnitude increase in IW energy
- Corresponding increase in sound speed variability –degrades signal coherence

Mesoscale modulation of cross shelf exchange in the Straits of Florida
D. Olson, H. DeFerrari, N. Shay and W. Johns
Progress in Oceanography

Focused arrivals in shallow water propagation in the Straits of Florida
H. DeFerrari, N. Williams and H. Nguyen
ARLO 4, 106 (2003)



Group Velocity COSH Profile w/ 75 m isovelocity layer



$$\beta^{-1}$$

SRBR BRB

Linear

1.0


-0.5

Cosh

1.2

0.0

$$c_o \cosh(g(1-z/D))$$



Ray/Mode Equivalence for β^{-1}



$$\text{Travel Time} = \int \frac{ds}{c(s)} \propto \frac{PL}{\langle c \rangle}$$

Travel Time dependence on Launch Angle:

Linear Profile $\langle c \rangle > \text{PL}$, $\beta^{-1} = -.5$

$\text{PL} > \langle c \rangle$, $\beta^{-1} = 1.0$

Cosh Profile $\langle c \rangle = \text{PL}$, $\beta^{-1} = 0.0$

$\text{PL} > \langle c \rangle$, $\beta^{-1} = 1.2$









Conclusion: All BRB eigenrays have exact same travel time at each range.

Frequency Dependence Model < > Measurements


FSPE

10 km range - f/100 RBR/SRBR modes





- 8 RBR and 8 SRBR @800Hz.
- 4 RBR and 4 SRBR @400 Hz.
- >
- 1 total @50 Hz.



Depth Dependence




PE Prediction: Pulse Response vs. Depth




PE Predictions for 3 Bottom Models

Monjo Bottom


Bottom C = 1580 m/sec.



Bottom C = 1620 m/sec.




Bottom C = 1720 m/sec.




PE Predictions for 3 Bottom Models

Monjo Bottom


Bottom C = 1580 m/sec.




Bottom C = 1620 m/sec.











Bottom C = 1720 m/sec.



FSPE



AO



AO Predictions:

2. Propagation by RBR and SRBR modes/rays. AO interested in SRBR as noise carrying paths.
3. Summer SS profile will narrow the arrival time spread of SRBR's
4. Total number of observable SRBR modes - approx = $f/100$. e.g. 4 @ 400 Hz. Only 1 mode for frequencies below 100 Hz.
5. Strong downward $C(z)$ gradients and absorbent bottom will result in very large TL for SRBR paths - difficult to measure at long ranges > 30km!
6. Temporal coherence times = >10 min → 1 hour+ for lower frequencies with SRBR 50% longer than RBR.
7. Horizontal coherence (radial, bottomed HLA) = > 100wavelengths. e.g. 1500m @100HZ.
8. Propagation model predictions match FSPE measurements best with slower 'Monjo' bottom model than with observed fast "Chapman" bottom. Geo-acoustic reasons unknown.
9. Many low-loss out-of-plane arrivals observed that possibly obscure the detection of low-level late SRBR arrivals. A potential practical problem for noise canceling algorithms.
10. AO measurements results may not differ much from those at FSPE site, (a modeling conclusion!)

SW06 Experiments – Mid-Atlantic Bight

MSM



19.7 km Range

85 m Depth



VLA



HLA

SHARK

MSM

M-Sequences


Center freq.		Band
4	Hz.	25
200		50
400		100
800		200
1600		400

VLA 16 phones




HLA 32 phones 468 m (15 m spacing)

SW06 Modes and Arrivals

Observed




Modeled




PE Prediction for AO

100 Hz. 25 Hz band 10 km.




Temporal Coherence

Temporal Coherence







Temporal Coherence








Coherence time (.75 level)

	BRB Group		SBRB arrival	
800Hz.	mean → 2.1	max → 6.5 minutes	mean → 2.8	max → 6.5 minutes
400Hz.	3.4	12.0	4.2	>30
200	8.3	> 30	15.0	>> 30








Temperature (deg. C)




Temperature (deg. C)




shru852 Temporal Coherence 100 Hz.Hr0200 7/29




shru852 Temporal Coherence 100 Hz.Hr 1200 7/29



shru2252 Temporal Coherence 100 Hz.Hr 2200 7/29



shru852 Temporal Coherence 100 Hz.Hr0800 7/30



Removing Phase Wrapping


Approach:

- Back out dT/dt
- Loop through small increments of linear time shifts and re-compute COH
- Look for maximum.


Each pulse $p(t)$ is time shifted by τ using the shifting theorem.

$$F^{-1}\left(F(p(t))e^{i\omega\tau}\right)$$


shru852 Pulse Response 100 Hz. Hr 200 7/29




shru852 Pulse Response 100 Hz. Hr 1200 7/29




shru852 Temporal Coherence 100 Hz.Hr0200 7/29




shru852 Temporal Coherence 100 Hz.Hr 1200 7/29




shru852 Temporal Coherence 100 Hz.Hr0200 7/29




shru852 Temporal Coherence 100 Hz.Hr 1200 7/29




shru252 Temporal Coherence 100 Hz.




shru853 Temporal Coherence 100 Hz.







Temperature (deg. C)




shru1851 Pulse Response 200 Hz. Hr 1800 7/28




shru451 Pulse Response 200 Hz. Hr 400 7/29




shru051 Pulse Response 200 Hz. Hr 1400 7/29




shru051 Pulse Response 200 Hz. Hr 2400 7/29




shru1051 Pulse Response 200 Hz. Hr 1000 7/30




Temperature (deg. C)




shru1851 Temporal Coherence 200 Hz. Hr 1800 7/28




shru451 Temporal Coherence 200 Hz. Hr 400 7/29




shru051 Temporal Coherence 200 Hz. Hr 1400 7/29




shru051 Temporal Coherence 200 Hz. Hr 2400 7/29





shru1051 Temporal Coherence 200 Hz. Hr 1000 7/30






Acoustic Observatory Receiving Arrays CALOPS Sept 07 Shipboard Suspended and Towed Transmissions


SWAP Station A 250 Hz. M-sequence






Time slice

Pulse response from 118 phones along the array




Signal Amplitude Data



$$COH(t, \tau) = \frac{\langle (p(t) * p(t + \tau))^2 \rangle_{\Delta t, \Delta T}}{\langle p(t)^2 \rangle_{\Delta t, \Delta T} \langle p(t + \tau)^2 \rangle_{\Delta t, \Delta T}}$$

Pulse response from 118 phones along the array



Change tau to dx - distance along the array

Same calculation yields spatial coherence for every arrival of the pulse response!


Steering the Array



Small shifts in travel time without distortion of the waveform

→ Fourier Time Shifting Theorem ←

$$p(t) \quad \Rightarrow FT \Rightarrow F(\omega)$$

$$F(\omega)e^{i\omega\tau} \quad \Rightarrow IFT \Rightarrow p(t-\tau)$$







Not aligned with wavefront

Phase changing along the array causing the coherence calculation to cycle.

Spatial Coherence AO 10 km 250 Hz.



Spatial Coherence




1. Lower order modes are more spatially coherent than higher order modes
2. All modes have **same** angle of arrival

Winter CALOPS 20 km 302 m Source Depth


Time

VC St A 20km 250 Hz. M-seq Pluse Arrival vs. Time




Dx Along array


Pulse Response Along Array A1 203m 20 km. 250 Hz




Spatial Coherence A1 203m 20 km 250 Hz




Spatial Coherence A1 203m 20 km 250 Hz




Spatial Coherence A1 203m 20 km 250 Hz




Spatial Coherence A1 203m 20 km 250 Hz




Spatial Coherence A1 203m 20 km 250 Hz




80 km m-sequence reception




Time slice



SWAP Station A 250 Hz. M-sequence




SWAP Station B 80 km 250 Hz. M-sequence








10 km



80 km





1. No recognizable modal structure
2. Burst of micro-paths
3. Different angles of arrival

Spatial Coherence

Higher order modes less coherent than lower order

Modes have varying arrival angles (horizontal)

Angular spread (horizontal) depends on range

<1 deg. @ 10 km

< 2 deg. 20 km

< 4-6 deg. 80 km

Publications

1. Observations of Low-Frequency Temporal and Spatial Coherence in Shallow water. DeFerrari.
Topic -- FSPE and AO data analysis of spatial and temporal coherence
Status – Submitted
5. Temporal Coherence of Mode Arrivals. DeFerrari, Lynch, Newhall.
Topic -- MSM to SHRU's transmission data analysis - temporal coherence
Status – Submitted
9. Spatial Coherence of Mode arrivals. DeFerrari, Colis, Duda, Newhall
Topic -- MSM to Shark - Coherence of mode arrivals.
Status – Early draft.
13. Acoustic Propagation on Shallow Shelves Inside of Retrograde and Progade Fronts.
Topic -- Comparison of internal wave fields and effects of propagation for two types of environments.
5. Limitations of Horizontal Coherence in Shallow Water.

