

Effects of internal waves on acoustic coherent communications during SW06

Aijun Song and Mohsen Badiey
University of Delaware

Arthur Newhall and James F. Lynch
Wood Hole Oceanography Institution


Harry A. DeFerrari
University of Miami

Introduction


- Internal wave effects on acoustic signals (Apel, *et al.*, JOE1997)
 - Intensity fluctuation (Badiey, *et al.*, JASA2005, JASA2007)
 - Temporal coherency variation (Rouseff *et al.*, JASA2002, Yoo, JOE2005)
- Internal wave effects on underwater acoustic communications
 - Expected effects but limited results in the literature
 - Current efforts: 1) concurrent acoustic and environmental measurement; 2) using our time reversal based receiver, 3) the extent of the effects

Experimental setting


- Internal wave event # 50:
18:00 (GMT) Aug 17 to
06:00 Aug 18, 2006
- Source: MSM
- Receiver: WHOI-VLA
- Range: about 20 km
- Water depth: about 80 m
- Acoustic signal:
~90 s M-sequences (BPSK
signals) at carrier
frequencies 813 Hz and
1627 Hz
- Source level: 186 dB re 1
micro Pa at 1 m
- Trans. Schedule: Every 30
min



Radar image




Water temperature profiles



Two environmental conditions

- 18:00: Internal waves had not reached the acoustic track (about 10 km away from the acoustic track)
- 22:30: Internal waves overlap the acoustic track



Receiver structure

- At the source, the transmitted signal in the baseband form is:

$$x(t) = \sum_n x(n) g(t - nT)$$


- The channel impulse response (CIR) function: dispersive (multipath), time varying

$$h^{(i)}(t, t)$$


- At the i-th element of the receiver:

$$y^{(i)}(t) = x(t) * h^{(i)}(t, t) + v(t)$$

Receiver structure



- Frequent channel estimation
- Soft output signal-to-noise ratio (SNR) of the decision-feedback equalizer (DFE) is the performance metric



-
- Receiver design:
 - Presented in A. Song, M. Badiey, H.-C. Song, W. S. Hodgkiss, M. B. Porter and the KauaiEx group, JASA2008, but without Doppler correction
 - Can achieve robust high data rate communications under dynamic ocean environments
 - Comparison with other time reversal/DFE methods (Edelmann, *et al.*, JOE2005, T. C. Yang, JOE2005, H.-C. Song, *et al.*, JASA2006)
 - Frequent channel estimation

Receiver parameters

- Key parameter: channel update interval
- Choose channel update interval:
 - Depending on the fluctuating rate of the channel: Fast fluctuating channels require small channel update interval

CIR function: 813 Hz

No internal waves(1800)

With internal waves(2230)



cir_800hz





10 km



80 km



Channel update interval for 813 Hz




CIR function: 1627 Hz

No internal waves(1800)

With internal waves(2230)

cir_1600hz


Channel update interval for 1627 Hz




-
- For 800 Hz carrier frequency:
 - Without internal waves, channel estimation can be performed every 8 s without loss of performance
 - With internal waves, channel estimation needs to be performed every 1 s
 - For 1627 Hz carrier frequency
 - Channel estimation needs to be performed every 250 ms regardless the internal wave condition

Channel
update interval:
250 ms

Frequency
dependency



(a) Temperature profiles recorded at the WHOI-VLA



(b) The output SNR of the communications receiver

Summary and future work

- Concurrent acoustic measurements and environmental observations
 - Significant internal wave effects on coherent underwater acoustic communications during a 12 h period at 813 Hz and 1627 Hz
 - Receiver parameters can be depended on the environment condition and the carrier frequency
 - Frequency dependency of the internal wave effects
-
- Acoustic modeling will be performed to explain the internal wave effects