

Simultaneous nearby measurements of acoustic propagation and high-resolution sound speed structure containing internal waves

Frank S. Henyey, Kevin L. Williams, Jie Yang,
and Dajun Tang

Applied Physics Laboratory, University of Washington

Experiment

Part of Shallow Water 2006 (SW06)

Measure environment and acoustic propagation together (2 ships + mooring)

Effect of Nonlinear internal waves (NLIW's)

Quantitative, deterministic computation of acoustic effects from NLIW's

Mid-frequency broadband acoustics: 1.5 to 10 kHz [0.13 ms resolution]



SWL
NOV 04
D-12000
S-18200

Data Collected

Aug. 13, 2006

Environmental measurements:

- Towed CTD chain ~ 50 CTD units, ~1 m vertical spacing

- 7 loops around acoustic path (1.5 loops with NLIW's)

- 2 s sampling @ 6 kts

- ship's GPS for positioning (R/V Endeavor)

- Ship's CTD profile ~ 1 hr before the NLIW's arrived (R/V Knorr)


Acoustic measurements:

- Broadband pulse every 13 s from R/V Knorr to MORAY receiver mooring


- 1 km acoustic path at 300° compass heading

- 80 m depth



Endeavor track & acoustic path




Distances from 73°W, 39°N



CTD profile @ 15:30



Acoustic Data



NLIW model


3. Find thermocline depth ($c = 1510$ m/s) for towed CTD every 2 s; low pass
5. Find front of both waves, back of first wave (2 m above deepest part)
7. Linearly interpolate in space & time from all 3 legs
9. Fill in linearly interpolated amplitude, back of wave 2 & bore (15 meters \rightarrow 17 m)
11. Connect with a smooth curve
13. Fill in the other sound speeds using 15:30 SSP
Vertically Lagrangian mode 1

Measured internal wave parameters

	Front of first wave	Back of first wave	Front of second wave
Speed	0.587 m/s	0.606 m/s	0.564 m/s
Bearing	324.3 _i	316.8 _i	331.4 _i
Time at 73W, 39N	15:14:26	15:19:57	15:23:01
Speed along acoustic path	0.643 m/s	0.632 m/s	0.658 m/s
Average		0.644 m/s	

NLIW model

3. Find thermocline depth ($c = 1510$ m/s) for towed CTD every 2 s; low pass
5. Find front of both waves, back of first wave (2 m above deepest part)
7. Linearly interpolate in space & time from all 3 legs
9. Fill in linearly interpolated amplitude, back of wave 2 & bore (15 meters \rightarrow 17 m)
11. Connect with a smooth curve
13. Fill in the other sound speeds using 15:30 SSP
Vertically Lagrangian mode 1





NLIW model


3. Find thermocline depth ($c = 1510$ m/s) for towed CTD every 2 s; low pass
5. Find front of both waves, back of first wave (2 m above deepest part)
7. Linearly interpolate in space & time from all 3 legs
9. Fill in linearly interpolated amplitude, back of wave 2 & bore (15 meters \rightarrow 17 m)
11. Connect with a smooth curve
13. Fill in the other sound speeds using 15:30 SSP

Vertically Lagrangian mode 1


Comparison of two reference frames



Following K. Lamb




Range-independent PE calculation (15:30)



Ray Trace with NLIW's

TB, BT, TBT, SBS arrivals



Modeling results

The ray trace captures the main features in the arrival time



~ 1 ms shortening of travel time when the ray turns in the thermocline and a wave coincides with that turning point

Passing through the thermocline has much less effect



Can we understand the systematic 1 ms shortening?

- 1. Ray path different (2nd order perturbation)*
- 2. Faster sound speed (1st order)*

Selected rays




TBT rays



TB ray

Interpretation ?



SBS ray: ~ 0 from path distortion, ~0.3 ms from ss change, events overlap

Conclusions

Towed chain measurements can be interpolated onto the acoustic path, but some assumptions are needed.

Acoustic modeling (PE & ray trace) obtains correct travel time.

Rays turning in the thermocline with a wave present are 1 ms faster

Attempted interpretation is partially successful

