

# Estimating geoacoustic properties of marine sediment on the New Jersey Continental Shelf from broadband signals


Yong-Min Jiang and N. Ross Chapman

University of Victoria, Victoria, BC, Canada

Work supported by ONR

# Objective :


Geoacoustic inversion using the chirp signals collected on the vertical leg of ARL 'L'-shape array at SWAMI32 site during SW06




- **MORAY site** (*JASAEI, IEEE, ASA 157*):
  - sediment sound speed and layer thickness
  - sediment attenuation estimate and its uncertainty
- **SWAMI32 site:**
  - check the information contents of the signals at two frequency bands
  - travel time inversion at two frequency bands

# Study site :

SWAMI32 site:  
ARL's L-shape  
array




Moray site:  
MPL's VLA1



Provided by Dr. John Goff

# Experiment:



## Experimental geometry:

- Water depth: 68.5m
- Range: 190 m
- Vertical leg of ARL array:
  - 10 hydrophones
  - separation: 5.95 m
  - depth: 10.3 ~ 63.85 m
- Source depth:
  - 6 depths: 10 to 60 m
  - extra depth at 25 m for low frequency transmission
- Angular coverage : 4 ~ 31.5°


### • Mid-frequency chirp transmission:

- Date: Sept. 03, 2006
- Frequency band: 1100 ~ 2900 Hz
- Time resolution: 0.49ms (0.37~0.43m)

### • Low-frequency chirp transmission:

- Date: Sept. 05, 2006
- Frequency band: 100 ~ 900 Hz
- Time resolution: 1.1 ms(0.8~0.95m)


# The environmental data:



Time line:

22:05, CTD  
 22:06, start (10 m)  
 .....  
 22:43, finish (60m)  
 00:25, CTD(JD247)

CTD cast for MF transmission




Time line:

13:08, CTD  
 13:28, start (10 m)  
 .....  
 14:10, finish (60m)  
 14:12, CTD  
 15:50, CTD

CTD casts for LF transmission


# The acoustic data: mid – frequency, 1100 ~ 2900 Hz

SWAMI-32, VLA, SD = 10 m, MF chirps




**SD = 10 m**

SWAMI-32, VLA, SD = 20 m, MF chirps




**SD = 20 m**

SWAMI-32, VLA, SD = 30 m, MF chirps




**SD = 30 m**

SWAMI-32, VLA, SD = 40 m, MF chirps




**SD = 40 m**

SWAMI-32, VLA, SD = 50 m, MF chirps



**SD = 50 m**

SWAMI-32, VLA, SD = 60 m, MF chirps




**SD = 60 m**

# The acoustic data


## low – frequency, 100~900Hz

Source depth: 25.0m, LF chirps




**SD = 25 m**

Source depth: 30.0m, LF chirps




**SD = 30 m**

Source depth: 40.0m, LF chirps




**SD = 40 m**

Source depth: 50.0m, LF chirps




**SD = 50 m**

Source depth: 60.0m, LF chirps




**SD = 60 m**

# For comparison – signals from Moray site frequency band: 1500 ~ 4500 Hz




# Data processing example (MF chirps, SD = 10m):

SWAMI-32, VLA, SD = 10 m, MF chirps




Source depth: 10.0m, MF chirps




**TVG**

# Simulation on the effect of the oceanic SSP for the 100 ~ 900 Hz chirps:



CTD **before** the transmission




CTD **after** the transmission

# Inversion strategy:

- **Geoacoustic model:** based on the resolvable layers in data
- **Forward acoustic model:** ray tracing
- **Inversion method:** adaptive simplex differential evolution
- **Energy function:**

$$E(m) = \sum_{i=1}^{N_L} \sum_{j=1}^{N_H} (\Delta t_{i,j} - \Delta T_{i,j}(m))^2$$

- **Water column SSP parameterization:**  
model the depth of the thermocline  
(for 100 ~ 900 Hz chirps only)



# Inversion scheme:

For 1100 ~ 2900 Hz chirps

once

- Use the SSP measured at the beginning of the 10 m source transmission and water column only arrivals to determine:  
**WD, Rng, RD and SD**
- Fix WD, Rng and RD

each depth

- Water column only arrivals for **SD** (and array tilt)
- Bottom and sub-bottom arrivals to determine:  
**sediment sound speed and layer thickness**

For 100 ~ 900 Hz chirps

- Use the SSP measured at the end of the 60 m source transmission and water column only arrivals to determine:  
**WD, Rng, RD and SD**
- Fix WD, Rng and RD

- Water column only arrivals for **SD and oceanic SSP**
- Bottom and sub-bottom arrivals to determine:  
**sediment sound speed and layer thickness**

# Preliminary inversion results:

100 ~ 900 Hz chirps, WD = 70.11m, Rng = 182.13m

SD (m)	Bounds	40	50
Inverted SD (m)	[SD-5, SD+5]	40.84	51.03
Water SSP (top layer depth) (m)	[17, 26]	Close to CTD@14:12	
Sediment sound speed (m/s)	[1550, 1750]	1680.1	1610.7
Layer thickness (m)	[1, 30]	4.1	7.3

1100 ~ 2900 Hz chirps, WD = 69.67m, Rng = 184.96m

SD (m)	Bounds	10	20	30	40	50	60
Inverted SD (m)	[SD-5, SD+5]	9.95	20.07	29.71	38.88	49.30	59.89
Array tilt (°)	[-5 5]	-1.26	-2.47	-2.78	-3.82	<-5	<-5
Sediment sound speed (m/s)	[1550, 1750]	1592.1	1632.1	1623.3	1647.8	-	-
Layer thickness (m)	[1, 30]	7.1	6.8	5.6	5.3	-	-

# Summary:

- No observation of the reflections from 'R' reflector in both frequency bands – implications?
- Not so consistent inversion results from the low and mid frequency data – low SNR and lack of spatial constrains
- compare with the inversion results with David Knobles *et al.* (JASAEEL 124, No.3 Pt.2, EL155)

Depth (m)	Sound speed (m/s)
0	1650
3.2	1653
3.2	1580
23	1600

# Acknowledgements:

- ONR for sponsoring the work
- Dr. David Knobles for providing the data