

# **Comparison of horizontal, vertical, and L-array signal processing: Application to shallow water ocean acoustics**

**D. P. Knobles, J. D. Sagers, and R. A. Koch**


**Work Supported by the Office of Naval Research  
Code 321 OA**

**158 TH MEETING OF THE ACOUSTICAL SOCIETY OF AMERICA  
24-28 October 2009 San Antonio, Texas**

# Inference of physical processes and parameter values on continental shelf


General Question/Issue Addressed: Compared to VLAs and HLAs, what additional **information** about the physical ocean environment can be inferred using 2-D and 3-D arrays?

Discussion today will focus on resolution of L-array relative to HA and VA



## Example: sound speed inversions?

If acoustic measurements can **infer information** about the seabed sound speed structure (and dispersion), then long range acoustic data can infer frequency dispersion of attenuation



But, how do we define *infer information*??

Claude Shannon



## Maximum Entropy in a Nutshell

Shannon or Gibbs Entropy

$$S = - \int_{\Omega} dW \rho(W|D) \ln [\rho(W|D) / \rho(W)]$$

$\delta S = 0$  subject to stated constraints

Edwin Jaynes



Constraints  $\int_{\Omega} dW \rho(W|D) = 1 \quad \int_{\Omega} dW C(W) \rho(W|D) = \langle C \rangle$

$$\rho(W|D) = \frac{\rho(W) \exp(-C(W, D)/T)}{Z}$$


Canonical Distribution

$$Z = \int_{\Omega} dW \rho(W) \exp(-C(W, D)/T)$$

- Compare resolution of value of seabed sound speed ratio  $R_1$  inferred from simultaneous signal processing of both HA and VA to separate processing of HA and VA of bottom mounted L-array recordings during Shallow Water 2006 experiment
- $\sigma_{R1}$  inferred from a MaxEnt approach
  - Coupling versus decoupling of first sediment layer with deeper layers
    - More layers than needed leads to better fits to data but greater uncertainty; compliments Occam's Razor
  - Various values for  $\langle C \rangle$  (how much importance do we attach to global minimum solution?)
  - If resolution with L-array is higher relative to HA only, what portion of VA contributes the most?

# L-Array Geometry


52-element L-array deployed during Shallow Water 2006  
on New Jersey continental shelf in ~ 70 m of water



## Signal Processing

HLA - complex beam spectra  
VLA - complex omni spectra

# Experimental set up for portion of SW06



# Representation, Assumptions, and Unknowns = 15

RV KNOOR Uniform motion ~ 4 km track



$f_1=59.8$  Hz,  $f_2=80.6$  Hz,  $f_3=136$  Hz,  $f_4=150$  Hz

52-element L-array

$SL(f_1), SL(f_2), SL(f_3), SL(f_4)$

Range at  $t_0$

Bearing at  $t_0$

Speed

Course

Water depth

Single Sound Speed Profile  
from measurement (potential  
large source of uncertainty)

VA offset

HA

Upper and lower bounds  
of ratio vary between silty sand  
and very coarse sand

**Ratio (1)**

Thickness (1)

$\rho_1 = 1.8$  g/cc  $\alpha_1 = 0.55$  dB/m@ 1 kHz  $\epsilon = 1.8$

**Ratio (2)**

Thickness (2)

$\rho_2 = 1.8$  g/cc  $\alpha_2 = 0.15$  dB/m@ 1 kHz  $\epsilon = 1.0$

**Ratio (substrate)**

$\rho_2 = 1.9$  g/cc  $\alpha_2 = 0.10$  dB/m@ 1 kHz  $\epsilon = 1.0$



$$C = \sum_{\text{center frequencies}} \frac{\sum_{\text{element pairs, sequences}} \left| \langle D_i D_j^* \rangle - |S_f| M_i^* M_j \right|^2}{N_{\text{CEN}} \sum_{\text{element pairs, sequences}} \left| \langle D_i D_j^* \rangle \right|^2}$$

Center Frequency Averaged Source Level  $\rightarrow |S_f|$   
 Center Frequency Model Cross Spectrum  $\rightarrow M_i^* M_j$   
 Center Frequency Averaged Cross-Spectral Data  $\rightarrow \langle D_i D_j^* \rangle$

$$\langle D_i D_j^* \rangle = |D_{\text{RL}}|^2 \sum_{\text{bins}} D_i D_j^* / |D_{\text{REF}}|^2$$

Cross Spectrum Normalization for Center Frequency Averaging

$$|D_{\text{REF}}|^2 = N_{\text{BINS}} \sum_{\text{elts}} |D_i|^2 / N_{\text{ELTS}}$$

Cross Spectrum Normalization for Center Frequency Average RL

$$|D_{\text{RL}}|^2 = \sum_{\text{bins,elts}} |D_i|^2 / (N_{\text{ELTS}} N_{\text{BINS}})$$

Minimization of Cost Gives SLs

$$|S_f| = \frac{\sum_{\text{element pairs, sequences}} \langle D_i D_j^* \rangle M_i^* M_j + \text{C.C.}}{2 \sum_{\text{element pairs, sequences}} |M_i^* M_j|^2}$$

# Signal Processing (cont)

Substituting for  $|s_f|$  gives correlation form of cost function:  $0 \leq C \leq 1$


$$C = 1 - \sum_{\text{center frequencies}} \frac{\left| \sum_{\text{element pairs, sequences}} \frac{\langle D_i D_j^* \rangle M_i^* M_j + \text{C.C.}}{2} \right|^2}{N_{\text{CEN}} \sum_{\text{element pairs, sequences}} |\langle D_i D_j^* \rangle|^2 \sum_{\text{element pairs, sequences}} |M_i^* M_j|^2}$$

incoherent sum over center frequency  
 ↓  
 coherent sum over pairs and sequences

Includes gain in the coherent sum over pairs and sequences to fit multipath arrivals and source track dependence.

Includes amplitude information to fit TL shape.

## Maximum likelihood seabed structure



Uncertainty arises from small fluctuations about average seabed structure

$$\text{Atten (dB/m)} = (f/1000)^{1.8}$$


with  $f$  in Hz

# HA only 3 m sediment lower limit, n=1


$$2\sigma_{R1} = 0.053$$

$$\sim (1637-1715 \text{ m/s})$$

$$\langle C \rangle = 1/2(C_{\min} + \bar{C}_u)$$



# VA only 3 m sediment lower limit, n=1




$$2\sigma_{R1} = 0.054$$

~ (1637-1715 m/s)

Note that  
<R1> and  $2\sigma_{R1}$   
remain  
approximately  
unchanged

# L-Array only 3 m sediment lower limit, n=1



$$2\sigma_{R1} = 0.050$$


~ (1628-1702 m/s)




# HA only 20 m sediment lower limit, n=1

$$2\sigma_{R1} = 0.045$$

~ (1632-1698 m/s)




# VA only 20 m sediment lower limit, n=1



$$2\sigma_{R1} = 0.041$$

~ (1635-1695 m/s)






$$2\sigma_{R1} = 0.039$$


~ (1636-1694 m/s)

$$2\sigma_{R1} = 0.034$$

~ (1640-1691 m/s)




# VA only 20 m sediment lower limit, n=.9



$$2\sigma_{R1} = 0.040$$

~ (1635-1695 m/s)



$$2\sigma_{R1} = 0.028$$

~ (1644-1686 m/s)





## Summary of ratio resolution with L-array for Ship of Opportunity Data in SW06

### Resolution of sound speed ratio $2\sigma$

Signal processing and lower bound on sediment thickness	HL processing only	VL processing only	HL+VL processing
3-m lower limit of 1st sediment layer 2 HL subapertures, $n=1$	0.053	0.054	0.050
20-m lower limit of 1st sediment layer 2 HL subapertures, $n=1$	0.045	0.048	0.039
20-m lower limit of 1st sediment layer 4 HL subapertures, $n=1$	0.048	0.048	0.040
3-m lower limit of 1st sediment layer 2 HL subapertures, $n=0.9$	0.052	0.057	0.040
20-m lower limit of 1st sediment layer 2 HL subapertures, $n=0.9$	0.034	0.040	0.028
		In all cases resolution increased using L-array	

- Current work
  - Quantified **increase in resolution** of sound speed ratio of seabed by doing simultaneous processing in vertical and horizontal dimension
  - Increase in resolution depends on assumptions
    - Representation of seabed
    - Proximity of importance sampling near global minimum;  $\langle C \rangle$
- Future and ongoing work
  - Estimation of  $\langle C \rangle$
  - New estimates of sound speed and attenuation dispersion and uncertainty from SW06
  - Apply to range-dependent cases
  - Design of future arrays (3-D) and experiments

## Phones 1 and 10



## Phones 14 and H

